INTERNATIONAL TELECOMMUNICATION UNION

ITU-T G.224

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

INTERNATIONAL ANALOGUE CARRIER SYSTEMS

GENERAL CHARACTERISTICS COMMON TO ALL ANALOGUE CARRIER-TRANSMISSION SYSTEMS

MAXIMUM PERMISSIBLE VALUE FOR THE ABSOLUTE POWER LEVEL (POWER REFERRED TO ONE MILLIWATT) OF A SIGNALLING PULSE

ITU-T Recommendation G.224

(Extract from the *Blue Book*)

NOTES

1 ITU-T Recommendation G.224 was published in Fascicle III.2 of the *Blue Book*. This file is an extract from the *Blue Book.* While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).

2 In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

© ITU 1988, 1993

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

Recommendation G.224

MAXIMUM PERMISSIBLE VALUE FOR THE ABSOLUTE POWER LEVEL (POWER REFERRED TO ONE MILLIWATT) OF A SIGNALLING PULSE [1]

The CCITT recommends that, for crosstalk reasons, the absolute power level of each component of a short duration signal should not exceed the values given in Table 1/G.224.

TABLE 1/G.224

Maximum permissible value, at a zero relative level point

Signalling frequency (Hz)	Maximum permissible power for a signal at a zero relative level point (microwatts)	Corresponding absolute power level Decibels referred to 1mW (dBm0)
800	750	-1
1200	500	-3
1600	400	-4
2000	300	-5
2400	250	-6
2800	150	-8
3200	150	-8

Note 1 - If the signals are made up of two different frequency components transmitted simultaneously, the maximum permissible values for the absolute power levels are 3 dB below the above values.

Note 2 - The values given in this table result from a compromise between the characteristics of various channel filters now in existence.

Reference

[1] CCITT Recommendation *Maximum permissible value for the absolute power level of a signalling pulse,* Vol. VI, Rec. Q.16.

---

[1] This Recommendation applies both to national and to international signalling systems.