TABLE 6/T.330

General value list

General value	Value attribute		
Name	Parameter name	Code [a)]	Format/Keyword
Call identification			Each component is separated by the character «/»
	TLMAU TID	T.61	Defined in Rec. F.200
	TLM TID	T.61	Defined in Rec. F.200
	Date and time	P	YY—MM—DD—HH:mm
	Document rel. No.	N	001 ~ 999
	Additional session rel. No.	N	01 ~ 99
Comments	—	P	
Date and time	—	P	YY—MM—DD—HH:mm
Frequency	—	N	In minutes
IPM identifier			<IPM Identifier>::=<OR Name>“/”<Local Message ID>“>”
	OR name		See OR name
	Local message ID	AI5	“LID=” <Local Message ID>
Message identifier	—	P	
Message length	—	N	In octets
Number of associated documents	—	N	
OR descriptor	OR name		See OR name
	Free form name	T.61	“Free Form Name=” <Free Form Name>|“FN=”<Free Form Name>
	Telephone number	P	“Telephone Number=” <Telephone Number>|“TEL=”<Telephone Number>

TABLE 6/T.330 *(cont.)*

General value	Value attribute			
Name	Parameter name	Code [a)]	Format/Keyword	Rema
			<OR Name>::=<Standard Attribute Lists><Domain Defined Attribute List>	
	Standard attribute list		<Standard Attribute List>::= "<" <**Keyword.Att**> (";" <**Keyword.Att**>)* ">"	
	Country name	N/P	"**Country Name**=" <Country Name> | "**CN**=" <Country Name>	Default: Co TLMAU
	Administration domain name	N/P	"**Administration Domain Name**=" <Administration Domain Name> | "**ADMD**=" <Administration Domain Name>	Défaut: AD la TLMAU
	Network adress	N	"**X121 Address**=" <Network Address> | "**X121**=" <Network Address> | "**Network Address**=" <Network Address>	
	Terminal identifier	P	"**Terminal ID**=" <Terminal Identifier> | "**TID**=" <Terminal Identifier>	
	Private domain name	N/P	"**Private Domain Name**=" <Private Domain Name> | "**PRMD**=" <Private Domain Name>	
	Organisation name	P	"**Organization Name**=" <Organization Name> | "**ON**=" <Organization Name>	
OR name	Numeric user identifier	N	"**User Agent ID**=" <Numeric User Identifier> | "**UAID**=" <Numeric User Identifier> | "**NUID**=" <Numeric User Identifier>	
	SurName	P	"**SurName**=" <SurName> | "**SN**=" <SurName>	
	Given name	P	"**Given Name**=" <Given Name> | "**GN**=" <Given Name>	
	Initials	P	"**Initials**=" <Initial> | "**I**=" <Initial>	
	Generation qualifier	P	"**Generation Qualifier**=" <Generation Qualifier> | "**GQ**=" <Generation Qualifier>	
	Organization unit name	P	"**Organization Unit Name**=" <Organization Unit Name> | "**OU**=" <Organization Unit Name>	
	Domain defined attribute listne		<Domain Defined Attributes List>::= "<DDA="<Type>","<Value>(";" <Type>","<Value>)* ">" | "<Domain Defined Attributes=" <Type> ","<Value>(";"<Type>","<Value>)* ">"	
	Type	P		
	Value	P		

TABLE 6/T.330 *(cont.)*

General value	Value attribute			
Name	Parameter name	Code [a)]	Format/Keyword	Remar
OR name (continued)	Postal address			
	PDS—name	P	“PDSN=” <value>	
	Physical delivery country name	N/P	“PDCN=” <value>	
	Postal code	N/P	“PC=” <value>	
	Physical delivery office name	P	“PDNA=” <value>	
	Physical delivery office number	P	“PDNU=” <value>	
	Extension OR address components	P	“EOA=” <value>	
	Physical delivery personal name	P	“PNP=” <value>	
	Physical delivery organization name	P	“ONP=” <value>	
	Extension physical delivery address components	P	“EPD=” <value>	
	Unformatted postal address	P	“UPA=” <value>	Max. 6 lines, 30 characters separated by
	Street address	P	“STA=” <value>	
	Post office box address	P	“POB=” <value>	
	Poste restante address	P	“PRA=” <value>	
	Unique postal name	P	“UN=” <value>	
	Local postal attributes	P	“LPA=” <value>	

TABLE 6/T.330 *(end)*

General value	Value attribute			
Name	Parameter name	Code [a]	Format/Keyword	
Retrieval identifier	—	N/P		
Subject	—	T.61		
Supplementary information	—	P		

[a] N = Numeric string in T.61 character set; P = Printable string in T.61 character set; AI5 = AI5 string in T.61 character set; T.61 = T.61 string.

[b] Descr.Att in OR Descriptor and Keyword Att in OR Name contains a Parameter—Id and a parameter—vaue. The Parameter—Ids appear with bold characters in this table.

Note 1 — Syntactical conventions are defined as follows and the character size does not make any sense:

<. . .> Represents a syntactical item, non—terminal

(. . .)* Iteration

| Exclusive or alternatives

“abc” Explicit characters abc.

Note 2 — Maximum length of parameter values can be found in X.400—Series Recommendations.